

Presented By: IQ Design Products

Contact Phone:

Customer Name:

Project Name:

Contact E-mail:

Fixture Type:



GE
Lighting

30899 - GE MR16

50MR16/Q/40/TL

Product Photo



GENERAL CHARACTERISTICS

Base Description	Turn and Lock
Base Type	Pin/Plug-In
Filament	C-6
Rated Life Hours-nominal	3500 h
Product Technology	Halogen
Base	GU7
Bulb Shape	MR16

PHOTOMETRIC CHARACTERISTICS

Beam Spread	40 deg
Center Beam Candle Pwr Candela	1395 cd
Color Temperature	3000 K

PRODUCT INFORMATION

Product Code	30899
Description	50MR16/Q/40/TL
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168994521
Standard Package GTIN	00043168308991
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	043168308991
Alternative Unit Of Measure	EACH
Standard Package Quantity	10
Ean UPC	043168994521
Standard Package GTIN	00043168994521
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
Sales Unit	Each
UCC	043168308991

DIMENSIONS

Diameter	2.0 in
----------	--------

ELECTRICAL CHARACTERISTICS

Input Voltage [nom]	12 V
Rated power (Watts)	50 W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Dispose of lamp in a closed container.

Do not use lamp if outer glass is scratched or broken.

Warning

Risk of Burn

Allow lamp to cool before handling.

A damaged lamp emits UV radiation which may cause eye/skin injury

Turn power off if glass bulb is broken. Remove and dispose of lamp.

Pressurized lamp--unexpected rupture may cause injury, fire, or property damage

Do not use lamp if outer glass is scratched or broken.

Risk of Fire

Keep combustible materials away from lamp.

Use in fixture rated for this product.

Jan 6, 2018 2:50:02 PM For additional information, visit www.gelighting.com