A19-4.5/9/14.5-E26-830-3WAY

Project:	Туре:	Prepared By:	Date:
USTED.	<image/> <image/> <image/> <image/> <image/> <text><text></text></text>	Constructed from Rated for use in e locations Frosted lens prod Longer lifespan co	Features and Benefits eplacement for incandescent and halogen lamps durable plastic which lowers risk of breakage enclosed and open fixtures in dry or damp uces smooth diffuse light ompared to legacy equivalents minimizes maintenance costs mpliant
Technical Sn	ecifications		

lechnical Specifications

Performance	L70 Lifespan:	Beam Angle:	
Product Type:	15,000-Hour LED lifespan based on IES LM-70	200° Electrical Power Factor: >0.9 Input Voltage: 120V	
A-Line 3 Way	results		
Input Wattage:	Construction		
4.5W/9W/14.5W	Bulb Shape:		
Lumens (Nominal):	A19		
500/900/1550	Enclosure Material:		
Color Accuracy:	Plastic	Operating Frequency:	
80	Housing Finish:	60 Hz Operating Temperature: -20°C - 40°C	
Color Temperature:	White		
- 3000K	Lens Finish:		
Dimmable:	Frosted		
Non-Dim	Base Type:		
-	E26		

Technical Specifications (continued)

Other

Equivalency:

40W/60W/100W

Technology EQ:

Incandescent

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty.</u>

Compliance

Safety Listing:

UL Listed

Environment/Fixture Rating:

Damp / Open

ENERGY STAR V2.0:

This product is ENERGY STAR $\ensuremath{\mathbb{B}}$ Version 2.0 Certified

Energy Star ID:

2367403

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

Model Number:

A10053(A19-4.5/9/14.5-E26-830-3WAY)

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity	
15.3 x 5.2 x 5.5	1	

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	0	0	0
PALLET	1764	0	0	0

