



Project:	Type:
Prepared By:	Date:

Technical Specifications		
<p>Construction</p> <p>Lens: Tempered, soda lime glass, 3mm thick (nominal 1/8"); can be sand blasted for additional diffusion</p> <p>Color: Fade-resistant color is molded into the glass</p> <p>Frame and L Rails: Die-formed 0.40 aluminum with powder-coated finish</p>	<p>LED Characteristics</p> <p>Light Loss Factor: 0.08</p> <p>Other</p> <p>Color Filter: Medium green</p> <p>Compatibility: FFLED 26W, 39W, 52W, 80W in white finish</p>	<p>Buy American Act Compliance: RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.</p>

Features
Simple to install or swap colors (4 screws for easy mounting)
Durable, tempered glass withstands outdoor use
Aluminum frame construction with RAB's durable, polyester power-coat finish

Ordering Matrix			
Family	Fixture	Filter Color	Frame Finish
CF	FF80	MG	W
	FX300 = FXLED300 FXLED200 FX150 = FXLED150 FXLED125 FXLED105 FXLED78 EZ78 = EZLED78 CANVAS78 FF120 = FFLED120 FF80 = FFLED80 FFLED52 FFLED39 FFLED26 FF18 = FFLED18	B = Blue LB = Light Blue G = Green MG = Medium Green LG = Light Green R = Ruby Red MR = Cherry Red MA = Medium Amber LA = Light Amber PP = Pale Purple Y = Yellow	A = Bronze W = White