

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

Technical Specifications		
Performance	Dimmable:	Construction
Product Type: HID Replacement	Yes	Bulb Shape: High bay (sensor)
Input Wattage: 60W/80W/115W	Compliance	Base Type: EX39
Lumens (Nominal): 8700/11600/16675lm	UL Listed: Suitable for damp locations	Endcap Material: Metal
Efficacy: 145 lm/W	Enclosed Fixtures: Suitable for use in enclosed fixtures	Enclosure Material: Polycarbonate
Color Accuracy (CRI): >80 CRI	DLC Model Number: H10058(HIDFA-115S-V-EX39-8CCT-BYP/3SP)	Beam Angle: 360°
L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results	DLC Listed: This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PLNAFK8CSGYM	
	LED Characteristics	
	Color Temperature: 3000K/4000K/5000K	

Technical Specifications (continued)

Electrical

Power Factor:

>0.9

Operating Temperature:

-30°C - 60°C

Input Voltage:

100-277V

Operating Frequency:

50/60 Hz

Electrical Characteristics

THD:

<20%

Flicker:

<30%

Installation

Installation Orientation:

Vertical

Other

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Wattage Equivalency:

200W/250W/400W Metal Halide or High Pressure Sodium

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
9.84 x 9.84 x 9.06	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	4	20.5	20.5	20.5
PALLET	64	48	40.95	45.77

Dimension

