

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

Technical Specifications		
<p>Performance</p> <p>Product Type: HID Replacement</p> <p>Input Wattage: 8.8-135W</p> <p>Lumens (Nominal): 1300-20000lm</p> <p>Efficacy: 147.7-148.1 lm/W</p> <p>Color Accuracy (CRI): 80 CRI</p> <p>L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results</p>	<p>Dimmable: Stepless dimming by rotate switch</p> <p>Compliance</p> <p>UL Listed: Suitable for damp locations</p> <p>Enclosed Fixtures: Suitable for use in open fixtures</p> <p>DLC Model Number: H10077(HIDFA-135S-V-EX39-8CCT-BYP)</p> <p>DLC Listed: This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PLV4B3FLLDON</p> <p>LED Characteristics</p> <p>Color Temperature: 3000K/4000K/5000K</p>	<p>Construction</p> <p>Bulb Shape: round</p> <p>Base Type: EX39</p> <p>Endcap Material: Aluminum</p> <p>Enclosure Material: Plastic</p> <p>Beam Angle: 90°</p>

Technical Specifications (continued)

Electrical

Power Factor:

0.9

Operating Temperature:

-30°C - 50°C

Input Voltage:

120-277V

Operating Frequency:

60 Hz

Electrical Characteristics

THD:

<20%

Other

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Wattage Equivalency:

400W Metal Halide or High Pressure Sodium

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	2	17.5	14.4	17.5
PALLET	36	44.49	36.61	45.67

Dimension

