



<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Durable die-formed steel frame and housing comes in a variety of colors and sizes making it easy to add multi-head recessed lighting to new construction projects

Color: White

Weight: 13.6 lbs

## Technical Specifications

### Listings

#### UL Listing:

Suitable for damp locations

### Construction

#### Housing Component:

This component must be ordered with the Multi-Head gear tray in order to make a complete fixture.

#### Housing:

Professional-grade, heavy-gauge steel construction with 1 1/4" spackle flange for trimless installation and three adjustment heights for gear trays.

#### Mounting:

Housing includes nailer bars and butterfly brackets. Brackets also accommodate mounting with 1/4" to 1/2" bar stock, C channel or 1/2" conduit.

#### Easy Installation:

Ceiling clamps install quickly and hold housing securely. Clamp ceilings from 1/2" to 2 1/2" thick, with coarse and fine adjustments.

#### Other

#### Trim:

Trimless

#### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish.

#### Country of Origin:

Designed by RAB in New Jersey and assembled in the USA by RAB's IBEW Local 3 workers.

#### Buy American Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

#### Recovery Act (ARRA) Compliant:

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

#### Trade Agreements Act Compliant:

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

#### GSA Schedule:

Suitable in accordance with FAR Subpart 25.4.

## Features

Adjustable clamps for quick, secure installation

Accommodates ceilings 1/2" - 2 1/2" thick

Butterfly bracket allows mounting with bar stock, "C" channel, 1/2" conduit or nailer bars