NDCANIC4R

RAB

Project:	Type:
Prepared By:	**Date:**

Driver Info

		LED Info	
Type:	N/A	Watts:	0W
120V:	N/A	Color Temp:	N/A
208V:	N/A	Color Accuracy:	N/A
240V:	N/A	L70 Lifespan:	N/A
277V:	N/A	Lumens:	N/A
Input Watts:	0W	Efficacy:	N/A
Efficiency:	N/A		

Color: N/A   Weight: 1.9 lbs

Technical Specifications

Listings

UL Listed:

Suitable for wet locations in a covered ceiling

Construction

IC Rating:

Suitable for direct contact with insulation

Housing:

Precision die cast aluminum

New Construction:

Nailer bars are provided for use with wood joist installations

Green Technology:

Mercury and UV-free. RoHS compliant components. Polyester powder coat finish formulated without the use of VOCs or toxic heavy metals.

Finish:

Formulated for high-durability and long lasting color

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions

RAB

Ordering Matrix

Family	Size	Shape
NDCANIC	4	R
	4 = 4"	**R** = Round
	6 = 6"	

Need help? Tech help line: **(888) RAB-1000** Email: **sales@rabweb.com** Website: **www.rabweb.com**

Copyright © 2018 RAB Lighting Inc. All Rights Reserved   Note: Specifications are subject to change at any time without notice

Page 2 of 2