



Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	14.00W
120V	0.13A	Color Temp	3500K (Warm Neutral)
208V	N/A	Color Accuracy	92 CRI
240V	N/A	L70 Lifespan	50,000
277V	N/A	Lumens	1,217
Input Watts	13.90W	Efficacy	87.6 LPW
Efficiency	N/A		

Technical Specifications

Listings

UL Classified:

Suitable for wet locations

ENERGY STAR V2.2:

This product is ENERGY STAR® Version 2.2 Certified.

Energy Star Model Number:

DLR0031

Energy Star ID:

2350039

NEC Compliant:

Suitable for use in closets. Compliant with NEC Sec. 410.16 (A)(1) and 410.16 (C)(3).

California Title 24:

Can be used to conform with the requirements of California Title 24 Part 6.

California Title 20:

Compliant LED Product

Electrical

Dimming Driver:

TRIAC compatible dimmer with dimming as low as 5%. [See dimmer compatibility guide here.](#)

THDi:

Produces less than 20% THD

PF:

≥0.9

Input Voltage:

120V

Operating Frequency (Hz):

60Hz

LED Characteristics

Lifespan:

50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

LEDs:

Long-life, high-efficacy, surface-mount LEDs

Wattage Equivalency:

100W Incandescent

R9 Value:

High color performance with R9 greater than or equal to 50

Flicker:

Silent and flicker free operations of less than 30%

Construction

Shape:

Round

Trim Style:

Baffle Trim

Housing:

Constructed from robust polycarbonate to prevent scratches and dents

Technical Specifications (continued)

Construction

Cold Weather Starting:

The minimum starting temperature is -30°C (-22°F)

Maximum Ambient Temperature:

Suitable for use in 40°C (104°F)

Lens:

Frosted polycarbonate diffusion lens. Regressed lens. Constructed from durable sheet metal construction.

Green Technology:

Mercury and UV free. RoHS-compliant components.

Mounting:

Easy installation with friction clips (4") and torsion springs (5"/6")

Socket Adapter:

Edison 26 Medium Base Socket adapter included in box

Compatible:

Compatible with most 5" and 6" recessed housings

Finish:

Matte White

Optical

Beam Angle:

95°±10°

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.


Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.


Case and Pallet Dimensions

	QTY	LENGTH	WIDTH	HEIGHT
CASE	4	15.47	7.99	7.95
PALLET	600	7.56	3.82	82.28

Dimension



Light Distribution



Features

- High Performance LEDS up to 106 lm/w
- Use to replace up to 100W traditional light sources
- Durable construction: dent and scratch resistant
- UL wet location rated
- Compatible with most standard recessed housings
- Dimmable down to 5% on compatible dimmers
- Available in 3 CCTs: 3000K, 3500K, 4000K
- Smooth diffusing regressed lens
- 5-Year, No-Compromise Warranty

Ordering Matrix

Family	Size	Shape	Wattage	CRI/Color Temp	Voltage	Dimming	Finish	Trim
R	6	R	14	935	120		W	B
	4 = 4" 6 = 6"	R = Round S = Square	7 = 600lm-700lm 8 = 700lm-850lm 10 = 850lm-1000lm 11 = 900lm-1050lm 14 = 1200lm-1400lm	940 = 90 CRI, 4000K (Neutral) 935 = 90 CRI, 3500K (Warm Neutral) 930 = 90 CRI, 3000K (Warm) 927 = 90 CRI, 2700K (Residential Warm) 840 = 80 CRI, 4000K (Neutral) 835 = 80 CRI, 3500K (Warm Neutral) 830 = 80 CRI, 3000K (Warm) 827 = 80 CRI, 2700K (Residential Warm)	120 = 120V UNV = 120-277V	Blank = TRIAC Dimming T = TRIAC Dimming	W = White	B = Baffle S = Smooth