



Replace conventional T8/T12 fluorescent tubes. Capable of single- or double-ended wiring for maximum in-the-field flexibility. Advanced driver technology reduces flicker and eye strain.

Color: White

Weight: 0.3 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Watts	7.00W	Input Voltage	120-277
Color Temp	3500K (Neutral White)	Power Factor	>0.9
Lumens	950	Flicker	<5%
Efficacy	135.7 LPW	THDi	N/A
Color Accuracy	80 CRI	R9	
L70 Accuracy	50,000		

## Technical Specifications

### Technical Specifications

**Product Type:**

Linear

**Bulb Shape:**

T8

**Nominal Length:**

2FT

**Finish:**

Frosted

**Wattage:**

7W

**Wattage Equivalency:**

17W Fluorescent

**Typical Lumen Output:**

950

**Efficacy:**

130 lm/W

**Color Temperature:**

3500K Neutral White

**CRI:**

80

**Base Type:**

G13

**L70 Lifespan:**

50,000 hours

**Operating Temperature:**

-20°C - 45°C

**Dimmable:**

No

**Beam Angle:**

180°

**Warranty:**

5-Year, No-Compromise Warranty

**Installation Type:**

Type B, Single or Double Ended wiring

**For Use in Emergency Fixtures:**

No

**For Use Outdoors in Open Fixtures:**

No

## Technical Specifications (continued)

### Electrical Characteristics

**Input Voltage:**

120-277V

**Power Factor:**

>0.9

**Operating Frequency:**

50 / 60 Hz

**Input Current @ 120V:**

68mA

**Input Current @ 277V:**

29mA

**Flicker:**

<5%

**THDi:**

≤25%

### Listings

**UL Recognized:**

Yes

**UL Classified:**

Yes

**NSF Listing:**

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones

**CEC Status:**

Lawful for sale in California