T8-7-24GC-840-DIR





Project: Type:

Prepared By: Date:

Replace existing T8 fluorescent tubes. Plug and Play tubes, no rewiring required with a shatter resistant coated glass construction

Color: White Weight: 0.3 lbs

Efficacy:

150 lm/W

CRI:

80

G13

Color Temperature:

4000K Cool White

Base Type:

L70 Lifespan:

Operating Temperature:

50,000 hours

-20°C - 45°C

Dimmable:

No

Driver Info LED Info

 Watts
 7.00W

 Color Temp
 4000K (Cool White)

 Lumens
 1,050

Efficacy 150 LPW
Color Accuracy 80 CRI

L70 Accuracy 50,000

Input Voltage Ballast Dependent Power Factor Ballast Dependent Flicker Ballast Dependent

THDi N/A

R9

Technical Specifications

Technical Specifications

Product Type:

Linear

Bulb Shape:

T8

Nominal Length:

2FT

Finish: Frosted

Wattage:

7\^/

Wattage Equivalency: 17W Fluorescent

Typical Lumen Output:

1050

Beam Angle:

180°

Warranty:

5-Year, No-Compromise Warranty

Installation Type:Type A, Plug and Play

For Use in Emergency Fixtures:

No

For Use Outdoors in Open Fixtures:

No

T8-7-24GC-840-DIR



Technical Specifications (continued)

Electrical Characteristics

Input Voltage:

Ballast Dependent

Power Factor:

Ballast Dependent

Operating Frequency:

Ballast Dependent

Input Current @ 120V:

Ballast Dependent

Input Current @ 277V:

Ballast Dependent

Flicker:

Ballast Dependent

THDi: ≤25%

Listings
UL Listed:

Yes

NSF Listing:

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones

CEC Status:

Lawful for sale in California