



The quality lighting your job site deserves. The LED work light that's built to perform.

Color: Yellow

Weight: 5.0 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type:	Constant Current	Watts:	120W
120V:	1.53A	Color Temp:	5000K (Cool)
208V:	N/A	Color Accuracy:	75 CRI
240V:	N/A	L70 Lifespan:	18000
277V:	N/A	Lumens:	14012
Input Watts:	130W	Efficacy:	108 LPW
Efficiency:	93%		

## Technical Specifications

### Listings

#### UL Listing:

Suitable for wet locations

#### IESNA LM-79 & LM-80 Testing:

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80

### LED Characteristics

#### LEDs:

Long-life, high-efficacy surface mount LEDs

#### Lifespan:

18,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

#### Color Stability:

LED color temperature is warrantied to shift no more than 200K in CCT over a 5 year period

#### Color Uniformity:

RAB's range of CCT (Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

### Electrical

#### Driver:

Constant Current, 120V: 1.53A

#### THD:

5.4% at 120V

#### Power Factor:

99.8% at 120V

#### Surge Protection:

2kV

### Construction

#### IP Rating:

Ingress Protection rating of IP65 for dust and water

#### Ambient Temperature:

-20°C to 40°C

#### Housing:

Aluminum

#### Thermal Management:

Superior thermal management with external Air-Flow fins

#### Lens:

Polycarbonate lens

#### Mounting:

Clip on carabiner

#### Gasket:

High temperature silicone

#### Green Technology:

Mercury and UV-free. RoHS compliant components

#### Finish:

Formulated for high-durability and long lasting color

### Other

#### 2 Yr Limited Warranty:

The RAB 2-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at

## Features

Portable solution for job sites

Impact resistant and protected against dust and water

Daisy chain capability

Carabiner hook for easy mounting

## Ordering Matrix

Family	Wattage	Wire Guard	Voltage
TEMPLED	120	G	/120/10CP
	100 = 86W 120 = 130W	G = Wire Guard	/120/10CP = 120V w/ 10ft Cord & Plug