



15" round die cast aluminum housing with vandalproof refractor for optimum parking garage light distribution. 150 or 175 w vertical mount Metal Halide or 100,000 hour Induction. Lamp supplied.

Color: N/A

Weight: 14.3 lbs

|                     |              |
|---------------------|--------------|
| <b>Project:</b>     | <b>Type:</b> |
| <b>Prepared By:</b> | <b>Date:</b> |

| Lamp Info    |         | Ballast Info |               |
|--------------|---------|--------------|---------------|
| Type:        | N/A     | Type:        | Elec HPF 120V |
| Watts:       | 55W     | 120V:        | 0.5A          |
| Shape/Size:  | N/A     | 208V:        | N/A           |
| Base:        | N/A     | 240V:        | N/A           |
| ANSI:        | N/A     | 277V:        | N/A           |
| Hours:       | 100,000 | Input Watts: | 60W           |
| Lamp Lumens: | 3,500   | Efficiency:  | 92%           |
| Efficacy:    | 58 LPW  |              |               |

**Technical Specifications**

**Listings**

**UL Listing:**

Suitable for wet locations. Fixtures can be wired with 90°C supply wiring if supply wires are routed 3" away from ballast.

**Construction**

**Mounting:**

Ceiling mount only. Not suitable for pendant mounting.

**Housing:**

Cast aluminum housing with 1/2 inch threaded NPS conduit access on 2 sides at 180° and the top of the housing.

**Housings:**

Die cast aluminum with powder coat bronze or white finish.

**Screws:**

Tamperproof center pin Torx-head and slotted Phillips head stainless steel screws provided. Be sure to order your Torx screwdriver (Catalog # VANDRIVER).

**Reflectors / Backplate:**

Heavy gauge cold rolled steel with high reflectance baked white enamel.

**Fluorescent Ballast Starting Temperatures:**

Electronic QT 0°F/-18°C NPF 120V 32°F / 0°C.

**Electrical**

**Sockets:**

HPS & MH Medium base 4kv Pulse Rated Glazed porcelain CFL Plug-in type, thermoplastic.

**Optical**

**Refractor:**

Injection molded polycarbonate, designed for maximum structural strength.

**Other**

**Buy American Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Buy American Act.

**Recovery Act (ARRA) Compliant:**

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

**Trade Agreements Act Compliant:**

This product is a COTS item manufactured in the United States, and is compliant with the Trade Agreements Act.

**GSA Schedule:**

Suitable in accordance with FAR Subpart 25.4.

**Features**

- Vertical lamp for better light disbursement and heat dissipation
- Both Vandal proof Center Pin Torx and slotted Phillips head screws supplied
- Tough polycarbonate refractors and Die cast aluminum housings
- Philips QL induction system with 100,000 hours available. Consult factory