



S11918

10T8/LED/48/840-850-865/DR/2PK

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	10W
Color Temperature:	4000K/5000K/6500K
Length:	48.00"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	10W
Volts:	120V-277V
Fluorescent Equivalent:	32W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	White
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	4000K/5000K/6500K
CRI:	83CRI
Lumen Output:	1800L

Dimmable:	Yes-Dimmable
Dimming Function:	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Beam Spread:	220D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to +45C (+113F)
Ballasting Requirements:	Ballast required, check compatibility
Bypass / Direct:	Direct
Ballast Type:	Type A
Tube Guard Use:	Not Approved
Safety Listing:	cULus - Listed
Technology:	LED
Material:	Glass

DIMENSIONS

MOL:	48.00"
MOD:	1.00"
Weight:	0.35

LISTINGS

Safety Listing:	cULus - Listed
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PWYOEL40
DLC Primary Use:	Replacement Lamps (plug and play) (UL Type A)
UL File Listing:	US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119187
Each Quantity:	2
Each Dimensions:	2.75 x 1.50 x 48.00"

Case UPC:	10045923119184
Case Quantity:	10
Case Dimensions:	49.20 x 6.10 x 8.10"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2023
Satco Products, Inc.
All Rights Reserved
April 10, 2023