



S11975

12T8/LED/48-835/DM/A-B

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	12W
Color Temperature:	3500K
Length:	48.00"
Base:	Medium Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	12W	Dimmable:	Non-Dimmable
Volts:	120V-277V	Beam Spread:	210D
Fluorescent Equivalent:	32W	Power Factor:	0.9
Shape:	T8	Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Filament:	LED	Ballasting Requirements:	Ballast required (Type A) or Ballast Bypass (Type B)
Base:	Medium Bi Pin	Bypass / Direct:	Dual
ANSI Base:	G13	Ballast Type:	Type A/B
Finish:	Frost	Safety Listing:	cULus - Classified; cULus - Certified; cULus - Listed
Housing Color:	White	Technology:	LED
Hours Rated:	50000H		
Color Temperature:	3500K		
CRI:	82CRI		
Lumen Output:	1700L		

DIMENSIONS

MOL:	48.00"
MOD:	1.00"
Weight:	0.49

LISTINGS

Safety Listing:	cULus - Classified; cULus - Certified; cULus - Listed
Location Rating:	Damp
Energy Star:	No
UL File Listing:	US/CN - E356817; US/CN - E335148
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923119750
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10"

Case UPC:	10045923119757
Case Quantity:	25
Case Dimensions:	50.00 x 6.00 x 6.00"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2022
Satco Products, Inc.
All Rights Reserved
May 22, 2022