



**S11985**

12T8/LED/36-835/BP/USA

**GENERAL SPECIFICATIONS**

Shape:	T8
Wattage:	12WW
Color Temperature:	3500K
Length:	35.78"
Base:	Medium Bi Pin



**TECHNICAL SPECIFICATIONS**

Wattage:	12W
Volts:	120V-277V
Fluorescent Equivalent:	25W
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	Frost
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	3500K
CRI:	82CRI
Lumen Output:	1400L

Dimmable:	Non-Dimmable
Beam Spread:	210D
Power Factor:	0.9
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast Bypass
Bypass / Direct:	BallastBypass
Ballast Type:	Type B
Single / Dual End:	Single Ended, Double Ended
Safety Listing:	cULus Classified; cRUus
Technology:	LED
Material:	Glass; Plastic

**DIMENSIONS**

MOL:	35.78"
MOD:	1.00"
Weight:	0.33

**LISTINGS**

Safety Listing:	cULus Classified; cRUus
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLF16HQKCCVD
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL File Listing:	E356871
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

**PACKAGING**

Each UPC:	045923119859
Each Quantity:	1
Each Dimensions:	36.00 x 1.00 x 1.00"

Case UPC:	10045923119856
Case Quantity:	25
Case Dimensions:	36.80 x 6.10 x 6.30"

110 Heartland Blvd.  
Brentwood, NY 11717  
PH 631-243-2022  
FX 631-243-2027

Distribution Centers  
New York, Florida,  
Texas, Washington,  
California, Puerto Rico

National Toll-Free  
800-43-SATCO  
(800-437-2826)  
www.satco.com

Copyright 2021  
Satco Products, Inc.  
All Rights Reserved  
October 24, 2021