



S16417

15T8/LED/HO-SIGN/42-865/BP
 15W T8 LED; 6500K; 2100 Lumens; 120-277V; Double Side
 LED; Type B; Ballast Bypass; Single Ended Wiring

Features

- Base rotates 90° for easy installation
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required



S16417

Item Number	UPC	Voltage	Watts	Operating Frequency	Power Factor	Lamp Shape	Base
S16417	045923164170	120-277	15	50/60Hz	0.90	T8	Recessed Double Contact HO/VHO

ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	Nominal Length	MOD In Inches	Initial Lumens
R17d	15T8/LED/HO-SIGN/42-865/BP	Non-Dimmable	Frosted	40"	42"	1.00"	2100

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type
50000	6500	Daylight	83	330	-30C (-22F) to a maximum of +45C (+113F)	10	Sleeve

CEC Status	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Lawful for sale in California	Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

