



S16441

42T8/LED/HO-SIGN/108-3CCT/BP/S

GENERAL SPECIFICATIONS

Shape:	T8
Wattage:	42W
Color Temperature:	4000K/5000K/6500K
Length:	105.81"
Base:	Recessed Double Contact HO/VHO



TECHNICAL SPECIFICATIONS

Wattage:	42W	Dimmable:	Non-Dimmable
Volts:	120V-277V	Beam Spread:	360D
Fluorescent Equivalent:	124W	Power Factor:	0.9
Shape:	T8	Operating Temp:	-20C (-4F) to +45C (+113F)
Filament:	LED	Ballasting Requirements:	Ballast Bypass
Base:	Recessed Double Contact HO/VHO	Bypass / Direct:	Ballast Bypass
ANSI Base:	R17d	Ballast Type:	Type B
Finish:	White	Single / Dual End:	Single Ended, Double Ended
Hours Rated:	50000H	Tube Guard Use:	No
Color Temperature:	4000K/5000K/6500K	Safety Listing:	cULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
CRI:	83CRI	Technology:	LED
Lumen Output:	5800L/6000L/5700L	Material:	Polycarbonate (PC)

DIMENSIONS

MOL:	105.81"
MOD:	1.13"
Weight:	1.76

LISTINGS

Safety Listing:	cULus - Classified; cRUus - Recognized Component; ETLus - SANITATION RECOGNIZED COMPONENT
Location Rating:	Damp
UL File Listing:	US/CN - E356817; US/CN - E335148; US/CN - E504973
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	ETL Sanitation listed (conforms to NSF)

PACKAGING

Each UPC:	045923164415	Inner UPC:	20045923164419	Case UPC:	10045923164412
Each Quantity:	1	Inner Quantity:	0	Case Quantity:	10
Each Dimensions:	108.00 x 1.15 x 1.15"	Inner Dimensions:	0.00 x 0.00 x 0.00"	Case Dimensions:	108.00 x 7.87 x 4.92"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2023
Satco Products, Inc.
All Rights Reserved
June 6, 2023