



S39391

22W/LED/HID/5000K/100-277V/E26
22 watt LED HID Replacement; 5000K; Medium base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP64 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 2.5KV

Shatter resistant materials, acceptable for use in food prep areas



S39391

| Minimum Compartment Size | | |
|--------------------------|--------|--------|
| Length | Width | Depth |
| 8.5 inch | 6 inch | 6 inch |

Optional Accessories

- In-line surge protector [80-929](#)
- Mog to med socket reducer (rated up to 250V) [92-406](#)

| Item Number | Product Line | UPC | Input Voltage | Watts | Operating Frequency | Incandescent Equivalent | Fluorescent Equivalent |
|-------------|--------------|-----|---------------|-------|---------------------|-------------------------|------------------------|
|-------------|--------------|-----|---------------|-------|---------------------|-------------------------|------------------------|

| S39391 | Hi-Pro | 045923303913 | 100 - 277 | 22 | 50/60Hz | 150W | 40W | |
|----------------|---------------------|-------------------------------|--------------------------------|----------------|-----------------------|-----------------------------|---|---------------|
| HID Equivalent | Base | ANSI Base | Lamp Code | | Dimmable/Non-Dimmable | Finish | MOL In Inches | MOD In Inches |
| 100W | Medium | E26 | 22W/LED/HID/5000K/100-277V/E26 | | Non-Dimmable | White | 5-11/16" | 2-3/8" |
| Initial Lumens | Average Rated Hours | Kelvin Temp | Color | CRI | Beam Spread Deg | Burning Position | Operating Temperature | |
| 3080 | 50000 | 5000 | Natural Light | 80 | 300 | Universal | -20C (-4F) to a maximum of +65C (+149F) | |
| Pack | Package Type | CEC Status | Material | RoHS Compliant | UL or ETL Listed | UL Classification | Warranty | |
| 48 | Box | Lawful for sale in California | Aluminum | Yes | Yes | cULus - Damp Location Rated | 5 Year Limited | |



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

