



S9976

15T8/LED/48-835/DR
15 watt T8 LED; 3500K; Medium Bi Pin base; 50000 Average rated hours; 2100 Lumens

Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Ballast required
- Solid State LED lighting
- High efficacy
- DLC Listed
- Compatible with emergency ballasts*
- All glass tube



S9976

*May not be compatible with all rapid start and emergency ballasts.

Ballast required

View:

[Ballast Compatibility Chart](#)

[Emergency Ballast Compatibility Chart](#)

This item has been discontinued.

Possible replacement:

- [S29976](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S9976	045923099762	15	25W-32W	T8	Medium Bi-Pin	G13	15T8/LED/48-835/DR
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color

Non-Dimmable	White	48"	1.00"	2100	50000	3500	Neutral White
CRI	Beam Spread Deg	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant	UL or ETL Listed
82	220	10	Box	Lawful for sale in California	PJ9Q2JJH DLC Search	Yes	Yes
UL Classification		Warranty		Status		Suggested Substitute	
cULus - Damp Location Rated		5 Year Limited		Discontinued		S29976	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com	Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico	Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027	
--	---	---	---