

SUPERLINE™ REFLEKTO™

MR16 ALUMINIZED REFLECTOR LAMPS


Superline™ Reflektto™ series of Halogen MR16 lamps provide professional accent lighting through evenly distributed light. The multi-lens geometry of the reflector surface in conjunction with an axial, computer-aligned filament, uniformly illuminates any surface. There is no ring-shaped shadow and no black spot in the middle of the light pattern.

The Superline Reflektto combines an aluminum deposition and a high temperature colored coating on the reflector to prevent any back-spill of light and to reduce heat to the back of the lamp. The aluminized coating redirects heat through the front of the lamp, thus diminishing the risk of thermal damage to sockets, transformers, and ceilings. The Superline Reflektto is offered in four designer colors of matte black, silver, bronze and chrome - ideal for low voltage cable and track lighting.



Available in - 20W, 35W, and 50W, in Flood and Narrow Flood beam spreads.



Standard Multi-Mirror Reflectors



Superline - Multi-Lens Reflector




GU5.3

The geometry of the Multi-lens reflector together with an axial filament design, guarantees an absolute uniform appearance across the beam without unsightly shadows, dark spots or rings. (All photos: 20W, flood distribution, taken 1 meter from screen).


FEATURES & BENEFITS:

- No Light Diffusion from Back-Spill
- Reduced Heat to Socket, Fixture and Transformers
- 80% Reduction of IR to the Back of the Lamp
- Decorative Aluminum Coating in Matte Colors Black, Silver, Bronze and Chrome
- Axial Filament for Precise Beam Control
- Dimmable
- Crisp White Halogen Light
- UV-Cut Halogen Capsule

Superline™ - Multi-Lens Reflector



Reflector Surface:
Optimized reflector design with hexagonal - shaped lenses



Reflector Cross Section:
The hexagonal-shaped lenses provide total uniformity of light distribution



Superline™ Reflektto™ lamps are manufactured under ISO 9001 guidelines ensuring quality and security for the purchaser.

APPLICATIONS:

- Accent Lighting
- Restaurants
- Museums and Galleries
- Shop Windows, Displays
- Track and Cable Lighting






SUPERLINE™ REFLEKTO™ MR16

MR16 Aluminized Reflector Lamps for General Lighting

Case Quantity: 50


Watts (W)	Ordering Code	Lamp Description	Voltage (V)	Dimension MOL (in)	Color Temp (K)	Beam Angle	Beam Spread	Luminous Intensity (cd)	Reflector Color Coating	Average Rated Life (h)
SUPERLINE™ REFLEKTO™ MR16 Aluminized Colored Back, 2-Pin Base										
20	1000007	BAB/B/FG	12	1.78	2900	36°	Flood	510	Black	3500
20	1000018	BAB/S	12	1.77	2900	36°	Flood	510	Silver	3500
20	1000019	BAB/S/FG	12	1.78	2900	36°	Flood	510	Silver	3500
35	1000554	FMV/B/FG	12	1.78	2950	24°	Narrow Flood	2000	Black	3500
35	1000567	FMW/B	12	1.77	2950	36°	Flood	1200	Black	3500
35	1000568	FMW/B/FG	12	1.78	2950	36°	Flood	1200	Black	3500
35	1003543	FMW/BZ/FG	12	1.78	2950	36°	Flood	1200	Bronze	3500
35	1000575	FMW/S	12	1.77	2950	36°	Flood	1200	Silver	3500
35	1000576	FMW/S/FG	12	1.78	2950	36°	Flood	1200	Silver	3500
50	1001652	EXZ/B	12	1.77	3000	24°	Narrow Flood	3000	Black	3500
50	1000425	EXZ/B/FG	12	1.78	3000	24°	Narrow Flood	3000	Black	3500
50	1003542	EXZ/BZ/FG	12	1.78	3000	24°	Narrow Flood	3000	Bronze	3500
50	1001653	EXZ/S	12	1.77	3000	24°	Narrow Flood	3000	Silver	3500
50	1000439	EXZ/S/FG	12	1.78	3000	24°	Narrow Flood	3000	Silver	3500
50	1000399	EXN/B	12	1.77	3000	36°	Flood	1580	Black	3500
50	1000400	EXN/B/FG	12	1.78	3000	36°	Flood	1580	Black	3500
50	1003541	EXN/BZ/FG	12	1.78	3000	36°	Flood	1580	Bronze	3500
50	1003819	EXN/CH/FG	12	1.77	3000	36°	Flood	1580	Chrome	3500
50	1000407	EXN/S	12	1.77	3000	36°	Flood	1580	Silver	3500
50	1000408	EXN/S/FG	12	1.78	3000	36°	Flood	1580	Silver	3500

All dimensions shown in inches unless otherwise noted.



Decorative Silver, Black, Bronze & Chrome Coating Stops Backspill of Any Light

The aluminum coating of the reflector ensures lower heat radiation to the rear of the lamp.



Lamp Socket

The model C-33U socket is rated up to 24V-7A for use with all low voltage USHIO GU5.3 based MR16 lamps. The metal clips secure the lamp firmly into the socket. Use Ordering Code 1002142.